

SN 09/757,784
Page 3

c. Amendments to the Claims

1. (Currently Amended) A measurement device for simultaneously measuring the position displacement of multiple locations on a target relative to a reference, the measurement device comprising:

a light source for producing a light beam;

optics for configuring the light beam as first and second differentiable beam portions, and for directing the first and second beam portions toward a target to be measured; and

a position sensitive detection component positioned-located to intercept first and second images created by simultaneous incidence of the first and second beam portions at first and second locations, respectively, on the target, and to provide output information representative of the position displacement of the target at the first and second locations relative to a reference based on the position of impingement of the first and second images on the position sensitive detection component.

2. (Currently Amended) The measurement device of claim 1, wherein the position sensitive detection component comprises first and second position sensitive detectors positioned to intercept the first and second images, respectively.

3. (Currently Amended) The measurement device of claim 2, wherein the first and second ~~detectors-locations~~ comprise ~~position sensitive detectors for providing an output signal representative of the position of the first and second beam images the same~~ location on the target.

4. (Original) The measurement device of claim 2, wherein the optics include a polarizer for causing the first and second differentiable beam portions to have first and second different polarizations and create differently polarized first and second images on the target, respectively, and wherein first and second detector optical paths are polarization sensitive with the first detector optical path capable of passing the polarized first image created by the polarized first beam portion on to the first detector and the second detector

SN 09/757,784
Page 4

optical path capable of passing the polarized second image created by the polarized second beam portion on to the second detector.

5. (Original) The measurement device of claim 4, wherein the detection component further comprises an imaging lens for focusing the differently polarized first and second images created by the first and second polarized beam portions, the imaging lens interposed between the target and the first and second detectors.

6. (Original) The measurement device of claim 5, wherein the detection component further comprises a partial reflector positioned to intercept the differently polarized first and second images, the partial reflector reflecting and directing at least part of one of the differently polarized first and second images toward one of the first and second detectors.

7. (Original) The measurement device of claim 6, wherein the partial reflector reflects and directs one of the differently polarized first and second images and passes the other.

8. (Original) The measurement device of claim 6, wherein the partial reflector comprises a beam splitter that splits the differently polarized first and second images, such that one part of each of the differently polarized first and second images is reflected resulting in differently polarized first and second reflected images, respectively, and another part of each of the differently polarized first and second images is passed through the beam splitter, resulting in differently polarized first and second passed images, respectively, and wherein one of the first and second detectors intercepts the differently polarized first and second reflected images and the other one of the first and second detectors intercepts the differently polarized first and second passed images.

9. (Original) The measurement device of claim 8, wherein the detection component further comprises first and second polarization analyzers interposed between the beam splitter and corresponding first and second detectors, respectively, one of the first and second analyzers intercepting and filtering the differently polarized first and second reflected

SN 09/757,784
Page 5

images to provide a first purified polarized image to the corresponding one of the first and second detectors, and the other one of the first and second analyzers intercepting and filtering the differently polarized first and second passed images to provide a second purified polarized image having a different polarization than the first purified polarized image to the corresponding other one of the first and second detectors.

10. (Original) The measurement device of claim 5, wherein the imaging lens comprises a plurality of imaging lenses configured to cooperate as a lens set.

11. (Currently Amended) The measurement device of claim 2, wherein the first and second detectors communicate with a microprocessor that calculates position displacement data for the first and second locations on the target relative to the reference.

12. (Original) The measurement device of claim 1, wherein the optics comprise a projection lens for focusing the light beam toward the target.

13. (Original) The measurement device of claim 12, wherein the optics further comprise a beam splitting device that splits the focused light beam into first and second differentiable portions.

14. (Original) The measurement device of claim 13, wherein the optics include a polarizer and wherein the first and second differentiable portions of the laser beam are polarized differently from one another.

15. (Original) The measurement device of claim 14, wherein the optics further include a beam directing device that directs the first and second differentiable portions in a desired direction.

16. (Original) The measurement device of claim 15, wherein the beam splitting device comprises the beam directing device and directs both first and second differentiable portions in substantially parallel paths toward the target.

SN 09/757,784
Page 6

17. (Original) The measurement device of claim 16, wherein the beam splitting device comprises a polarized beam splitting component and a reflecting component.

18. (Original) The measurement device of claim 17, wherein the beam splitting device comprises a polarizing beam splitter that splits the light beam into first and second polarized beam portions and directs the second beam portion toward the target, a quarter wave plate that rotates at least the first beam portion, and a movable mirror that reflects the rotated first beam portion back through the quarter wave plate and toward the target ~~parallel to the second beam portion, the quarter wave plate again rotating the~~ previously rotated first beam portion such that the rotated first beam portion is 90 degrees out of phase with the second beam portion.

19. (Original) The measurement device of claim 18, wherein the detection component further comprises:

first and second polarization sensitive detectors positioned to intercept the first and second images, respectively;

an imaging lens for focusing the differently polarized first and second images created by the first and second polarized beam portions, the imaging lens interposed between the target and the first and second detectors;

a partial reflector interposed between the imaging lens and the first and second detectors and positioned to intercept the differently polarized focused first and second images, the partial reflector including a beam splitter that splits the differently polarized first and second images, such that one part of each of the differently polarized first and second images is reflected resulting in differently polarized first and second reflected images, respectively, and another part of each of the differently polarized first and second images is passed through the beam splitter, resulting in differently polarized first and second passed images, respectively; and

first and second polarization analyzers interposed between the beam splitter and first and second detectors, respectively, the first analyzer intercepting and filtering the differently polarized first and second reflected images to provide a first purified

SN 09/757,784
Page 7

polarized image to the first detectors, and the second analyzer intercepting and filtering the differently polarized first and second passed images to provide a second purified polarized image having a different polarization that the first purified polarized image to the second detectors.

20. (Original) The measurement device of claim 18, wherein the movable mirror is adjustable to space the first and second locations on the target relative to each other.

21. (Original) ~~The measurement device of claim 15, wherein the beam~~
splitting device comprises a Wollaston prism and wherein the beam directing device comprises first and second movable mirrors.

22. (Original) The measurement device of claim 21, wherein the beam directing device further comprises a reflecting cube interposed between the first and second movable mirrors and the target, wherein the first and second beam portions are reflected by the first and second movable mirrors, respectively, toward the reflecting cube, and wherein the reflecting cube directs the first and second beam portions in parallel toward the target.

23. (Original) The measurement device of claim 22, wherein the first and second movable mirrors are both adjustable to space the first and second locations on the target relative to each other.

24. (Original) The measurement device of claim 23, wherein the detection component further comprises:

first and second polarization sensitive detectors positioned to intercept the first and second images, respectively;

an imaging lens for focusing the differently polarized first and second images created by the first and second polarized beam portions, the imaging lens interposed between the target and the first and second detectors;

a partial reflector interposed between the imaging lens and the first and second detectors and positioned to intercept the differently polarized focused first and second images, the partial reflector including a beam splitter that splits the differently polarized first

SN 09/757,784
Page 8

and second images, such that one part of each of the differently polarized first and second images is reflected resulting in differently polarized first and second reflected images, respectively, and another part of each of the differently polarized first and second images is passed through the beam splitter, resulting in differently polarized first and second passed images, respectively; and

first and second polarization analyzers interposed between the beam splitter and first and second detectors, respectively, the first analyzer intercepting and filtering the differently polarized first and second reflected images to provide a first purified polarized image to the first detector, and the second analyzer intercepting and filtering the differently polarized first and second passed images to provide a second purified polarized image having a different polarization than the first purified polarized image to the second detector.

25. (Original) The measurement device of claim 24, wherein the optics further comprise a mirror movement mechanism for moving the movable mirrors.

26. (Original) The measurement device of claim 25, wherein the detection component further comprises a detector movement mechanism for moving the first and second detectors.

27. (Original) The measurement device of claim 26, wherein the mirror movement mechanism is coupled to the detector movement mechanism such that movement of the movable mirrors to alter spacing of the point on the target results in movement of the detectors for interception of the first and second images.

28. (Original) The measurement device of claim 27, wherein the detector movement mechanism comprises a pivotally mounted T-bar linkage that is pivotally coupled to the mirror movement mechanism, movement of the mirror movement mechanism resulting in direct movement of the first and second detectors, each at an angle relative to the movement of the mirror movement mechanism.

SN 09/757,784
Page 9

29. (Original) The measurement device of claim 28, wherein the angle comprises 45 degrees.

30. (Original) The measurement device of claim 27, wherein the detector movement mechanism comprises a cam action mechanism coupled to the mirror movement mechanism, movement of the mirror movement mechanism resulting in direct movement of the first and second detectors, each at an angle relative to the movement of the mirror movement mechanism.

31. (Original) The measurement device of claim 30, wherein the angle comprises 45 degrees.

32. (Currently Amended) A method of measuring a z-height distance relative to a reference at two locations on a disk drive head suspension, the method comprising the steps of:

providing a light beam;
splitting the light beam into first and second differentiable beam portions;
directing the first and second differentiable beam portions toward the two locations to be measured on the head suspension, and causing the beam portions to be reflected from the head suspension, wherein paths of the beam portions vary as a function of the z-height of the two locations with respect to the reference;

intercepting first and second images created by simultaneous incidence of the first and second differentiable beam portions on the target with a position sensitive detection component; and

analyzing ~~positional-displacement~~ data collected by the position sensitive detection component based upon a location of interception of the first and second images by the position sensitive detection component to calculate a desired z-height distance measurement for the two locations on the head suspension relative to a reference.

33. (Original) The method of claim 32, further comprising the steps of:

AI
(m)

SN 09/757,784
Page 10

focusing the light beam after the step of splitting; and
focusing the first and second images prior to the step of interception.

34. (Currently Amended) The method of claim 32, wherein ~~the step of intercepting further includes detecting the positions of the first and second images with the detection component~~ two locations are different locations on the target.

35. (Currently Amended) The method of claim ~~34~~32, wherein the detection component comprises first and second position sensitive detectors, and wherein the step of detecting includes providing an output signal from the first and second position sensitive detectors representative of the position of the first and second images, respectively.

36. (Original) The method of claim 32, wherein the step of splitting includes passing the light beam through beam splitting optics to create the first and second differentiable beam portions.

37. (Original) The method of claim 36, wherein the beam splitting optics include a polarizer, and wherein the step of splitting includes splitting the light beam into first and second beam portions having first and second different polarizations, respectively.

38. (Original) The method of claim 36, wherein the beam splitting optics includes a beam directing device, and wherein the step of directing comprises interacting the first and second beam portions with the beam directing device to direct the first and second beam portions toward the head suspension.

39. (Original) The method of claim 38, wherein the beam directing device comprises a movable mirror, and wherein the step of directing comprises reflecting at least one of the first and second beam portions off the movable mirror toward the head suspension.

40. (Original) The method of claim 39, further comprising the step of adjusting the two locations on the head suspension by moving the movable mirror.

SN 09/757,784
Page 11

41. (Original) The method of claim 38, wherein the beam splitting optics comprises a Wollaston prism and the beam directing device comprises two movable mirrors, and wherein the step of splitting includes passing the light beam through the Wollaston prism to create first and second differently polarized beam portions that are then, in the step of directing, reflected off the two movable mirrors.

42. (Original) The method of claim 41, wherein the beam directing device further comprises a reflecting cube interposed between the two movable mirrors and the head suspension, ~~and wherein the step of directing further includes passing the first and second~~ polarized beam portions reflected by the two movable mirrors through the reflecting cube creating first and second parallel polarized beam portions directed toward the head suspension.

43. (Original) The method of claim 42, further comprising the step of adjusting the two locations on the head suspension by moving at least one of the two movable mirrors.

44. (Original) The method of claim 42, further comprising the step of adjusting the two locations on the head suspension by moving both of the movable mirrors.

45. (Original) The method of claim 44, further comprising the step of adjusting the position of the detection component relative to movement of the movable mirrors so as to maintain focus of the first and second images intercepted by the detection component.

46. (Original) The method of claim 45, wherein the step of adjusting further comprises coupling the positional movement of the detection component directly to movement of the movable mirrors to achieve automatic adjustment of the position of the detection component upon movement of the movable mirrors.

47. (Currently Amended) A method of measuring a distance ~~from between~~ a target and a reference comprising the steps of:

SN 09/757,784
Page 12

AI
encl

providing a light beam;
splitting the light beam into a plurality of differentiable beam portions;
directing the plurality of differentiable beam portions toward a target to
be measured;

detecting images created by simultaneous incidence of the plurality of
differentiable beam portions on the target using position sensitive detecting components; and
analyzing the output of the position sensitive detecting components due
to the location of the detected images on the position sensitive detecting components to
calculate a desired distance measurement from between the target and the reference.
